

Translation from the German Original **Operating manual**

BRAUMEISTERmobil

WIFI/Firmware updater module Art No.: 77455



Last updated: January 2019



3	GENERAL	1
3	SAFETY INSTRUCTIONS:	2
4	COMPONENTS AND SCOPE OF DELIVERY	3
4	TECHNICAL DATA	4
4	DISPOSAL	5
5	QUICK REFERENCE GUIDE	6
6	CONNECTING TO THE BRAUMEISTER	7
6	UPDATE FIRMWARE	8
7	SETTING UP A WIFI CONNECTION	9
8	USING THE ONLINE SOFTWARE FOR BREWING	10
9	TROUBLESHOOTING	11
10	GUARANTEE CONDITIONS, HANDLING A GUARANTEE	12



1 General

Dear customer,

You have purchased a new device from our company. Thank you for your trust in our product. Quality and functionality of our products rate high on our list of priorities.

Intended use:

The BRAUMEISTERmobil module is designed to be connected to the brewing controller on the Braumeister Generation 2015 to both update the firmware and monitor the brewing process over WIFI.



Operating manual:

We have compiled this manual to ensure the reliable and safe commissioning and operation of the module right from the start. Please read the manual carefully and completely before continuing with the installation.



Declaration of conformity:

We, at SPEIDEL Tank- und Behälterbau GmbH, hereby declare that the product - BRAUMEISTERmobil - described in this manual and to which this declaration refers, complies with the policies of the following European Directives:

- Radio equipment and telecommunications terminal equipment 1999/5/EC
- Electromagnetic compatibility 2004/108/EC,
- Low voltage 72/23/EEC

Network standard: IEEE 802.11 b/g/n ETSI EN 300 328 V1.8.1

Distributor:

Speidel Tank- und Behälterbau GmbH Krummenstrasse 2 72131 Ofterdingen Germany www.speidels-braumeister.de www.speidel-behaelter.de

2 Safety instructions:



• Only use the Braumeister in conjunction with the WIFI module when you can regularly monitor it personally. This means you should only use the module inside your own company WIFI network. Always make sure that the Braumeister is properly set-up and filled with water before starting the pump and heating it up over the WIFI module. Fire hazard!



• When performing cleaning activities on the Braumeister and the WIFI module, always ensure that the plug is disconnected (disconnection from the mains). Do not spray the device down or allow spray to come into contact with electric components. **Danger of electric shock!**



• After removing and unplugging the module on the reverse side of the Braumeister controller, you should close the plug connection again with the dummy cap to prevent water or contamination entering. **Danger of electric shock!**



• For the sake of their safety, keep any packaging (cardboard, polystyrene, etc.) out of the reach of children at all times. Do not allow small children to play with foil. Danger of **suffocation**!

3 Components and scope of delivery

The delivery package contains the module housing in black anodised aluminium with a mounting clamp on the reverse side, adjustable external antenna and a 40cm long cable fitted with a cable gland. A USB connection cable for connecting the WIFI module to a PC in also included in delivery.



4 Technical data

Network standard: IEEE 802.11 b/g/n

Max data rate: 65 Mbit/s

Software update: Minimum system requirements: Windows 7

Security standard: WPA2 (default setting)

Protection class: IP 40

5 Disposal



Meaning of the "refuse bin" symbol on the module: Protect our environment; electrical appliances should never be disposed of in your household waste. Make use of the collection depots provided for disposing of electrical appliances and deposit any electrical appliances you no longer require at these depots. You can get information on where to dispose of your old appliances from your local authorities.



6 Quick reference guide

We have briefly summarised the individual steps for setting up the WIFI module below. Each individual step is explained in detail in the sections that follow:



Remove the WIFI module from the protective carton and mount it on a Braumeister base. Plug the cable gland into the free socket on the reverse side of the Braumeister controller and tighten (connect the temperature sensor as well).

Update the firmware. At least Version 1.1.27 should be installed on the device to be able to use the WIFI module (you can see the version number clearly in the *Settings* menu). To do so, download the update software and the latest firmware version from our website at www.speidels-braumeister.de/downloads.html You will find all the files in the .zip file stored in one folder.





Connect the module (port on the side of the module) to your PC using the USB cable. Wait until you operating system automatically finds a suitable driver and installs it. You should then connect the Braumeister to the mains. Launch the software updater and transfer the latest firmware (hex file) to the controller. Unplug the Braumeister and remove the USB cable. The latest version should now be on the controller.

Go to Settings and then WIFI. Click on Scan to search for available networks. Select the most suitable network, enter your password (max. 31 signs) with the arrow keys, if necessary delete detached signals/blank space with Abandon and click on Connect. The controller shows an IP address if a connection is made. Then move to Register and type in the email address which belongs to your MySpeidel account. Look after correct orthography! With MySpeidel you can sync recipes to the Braumeister and monitor the whole brewing process.





7 Connecting to the Braumeister



Remove the WIFI module from the carton and clip the module to the side-base on the Braumeister using the clamp on the reverse side of the module. In the beginning, this type of clamp is always very stiff, in order to make sure that module remains tightly clamped to the base. The module is clamped to the side of the controller on the 2001 and 5001 operating models. On the reverse side of the controller on the new 2015 generation, you will find another screw connector next

to temperature sensor connector. Plug the module into this connector and screw it tight. The module is now ready for further use.

8 Update firmware



Go to www.speidels-braumeister.de/downloads.html and download the *Braumeister Software Updater* .zip file to your PC. Unzip the files and save them all in a single folder. The .zip file contains the *Software Updater*, driver (only required if your operating system fails to find the driver automatically) and latest firmware version of the Braumeister controller, $BrewControl_x.hex$.

The USB cable included in delivery is used to connect your PC and the WIFI module. Open the rubber cap on the side of the module and connect the mini-USB. Plug the other end into a free USB port on your PC. The Braumeister controller is still not connected to the mains. Have your operating system (e.g. Windows 7 or higher) search for a driver for the USB connection automatically.



Connect the Braumeister controller to the mains. The screen remains blank. Now launch *Software Updater.exe*, select the port which connects the Braumeister to your PC and click on *continue*. Then select the path to the latest firmware version, which should be in the same folder as the updater.



Click on *Update*. The latest version will now be transferred to your device. This may take several minutes. If the software reports a successful update, unplug the USB cable from the PC and the module, disconnect the Braumeister from the mains, wait a few seconds and then reconnect the controller to the mains. The screen becomes bright again, displays a *Launch Wifi* message and should now have the latest software version installed (visible under *Settings* right on the top).



9 Setting up a WIFI connection



The requirement for using WIFI with MySpeidel.com is firmware version 1_1_27 or higher (the version number can be seen at the top right under *Settings*). Go to Settings and then click on WIFI.

Run a full scan first to find the WIFI networks available in your area. Make sure that your preferred wireless router is in operation. The controller now lists the networks found (go to *Enter SSID* to verify/modify the advanced settings for the WIFI network. Security standard: only to be used if the automatic connection

fails to function). It's recommended to use WPA2 on the router and the Braumeister control.



DHCP to enter the correct data).

Select the network you wish to use using the arrow keys, and enter the WIFI password under PSK (Pre-shared key) with the same arrow keys (max. 31 signs) Click on *Select* to confirm each digit/number. After entering the last number/digit, go to *Connect* using the arrow keys. Please make sure that there is no blank space or pre-set ciphers behind your password. If necessary, delete them with *Abandon* before proceeding (otherwise malfunction message *OAEB* will occur, if the IP address fails to be assigned automatically or it has been changed, then go to



Use the arrow button to move to Register and type in the mail address which belongs to your MySpeidel account. Be sure of the correct letters and numbers. Also think about big and small letters as well as special characters and blank spaces.

Then you will receive a confirmation mail with a link to activate your device (consider also your SPAM folder). Now it's possible to rename it or to manage it in the device settings. The Braumeister is ready to use it in

MySpeidel. You can now use some of the functions of your Braumeister over the device (e.g. Start recipe) and, above all, monitor the status of the device (Monitoring).



<u>Caution:</u> Make sure no unwanted switching on the pump and/or heater takes place. Make sure that the water has been topped up before starting a recipe. Make sure that combustible materials are kept well away from the brewing device. Use the web connection always near the usage site of the Braumeister to make sure you are in range of the device and can intervene if necessary.



10 Using the online software for brewing



Go to www.myspeidel.com and create your own account. Now you can edit your devices, develop, save and share your recipes and also sync it to your Braumeister. Further devices like Gärmeister or GÄRSPUNDmobile are managed with this account.



On MySpeidel you can call up the monitoring software and with some delay the data from the controller will be displayed.

In the yellow status bar at the top, you will find the most important information on the Braumeister status, such as temperature, connection status and last update. The data is routinely updated every few seconds. The display is responsive and is displayed optimally both horizontally and vertically.



An image of the Braumeister controller is displayed. You can intervene in a controlled manner by starting a recipe, or manually, by turning the heater and pump on/off. Changing settings are made at the device manually and recipes are changed and developed with MySpeidel. In an emergency, the programme can also be stopped and terminated online.

When selecting and starting a recipe, the time-line for the entire brewing process appears in addition to controller view. Here you can see more easily at what stage in the process you are at, and which phases are still pending. Novices can access additional video and text-based information about the individual brewing phases by clicking on the Information icons.

The language for the software is defined by the language selected on the Braumeister controller (English, German, French, Spanish). If you want to change the language and you have already used the software in another language, you first need to delete the chronicle on the device and open the software again by re-entering the IP address.



11 Troubleshooting

Problems when brewing:	Troubleshooting
Firmware fails to update	If the operating system on your PC fails to find a
	driver independently, then use the driver supplied in
	the .zip file you have downloaded. Run the CDM.exe
	file. Be sure that all files are in the same folder.
The BRAUMEISTERmobil software fails	Make sure that the WIFI is connected to the Internet.
to load	
The Updater-Software cannot recognize	The software proceeds by running the first 8 ports.
the correct Port (COM-connection)	Please make sure that the connection cable is attached
	to one of the first eight ports. The new Updater
	delivered with 1.1.24 finds port up to 99.
Update is canceled after 25% and reports	Make sure the Braumeister is connected to a power
successful update when actually there is	source during the whole updating process (display
no firmware version on the device	remains black)
WIFI connection cannot be established	Check if the password you entered is correct.
	Check if a common security standard is used. To do
	so, go to Enter SSID. You can manually change all
	the data for the network here.
The Internet-software	Make sure your router is allowing the communication
BRAUMEISTERmobil is loaded while	of several WIFI devices among themselves.
there is no data being sent from the	See safety instructions in the WIFI-range of the
Braumeister.	router.
Return of the IP address 0.0.0.0	Safety-standards are not the same. Please insert the
	data manually in the menu DHCP of the Braumeister.
Pour connection	Check the antenna if screwed correctly and plane and
	be sure that the antenna connection to the device is
	with a pin in the middle.
Error code OAEB	The password has not been inserted correctly. Check
	your password. Make sure there is no blank space or
	pre-set ciphers after your password, if your password
	does not fill the whole length. Delete with <i>Abandon</i> .
Error code 08F8	Password error
Error code 0AFD	Security standard of the WIFI is not the same
Error code 0XF4	A wrong character/ sign is used on the router which
	cannot displayed the Braumeister
Error code 0701	Too long password (max. 31 signs) or too long router
	name.
"Only visible with newest firmware" or	No or wrong mail address on the control unit oft he
missing buttons in the mobile control	Braumeister – at REGISTER in the Wifi settings.
window	



12 Guarantee conditions, handling a guarantee

Conditions:

- Statutory guarantee conditions apply. The guarantee period for users is reduced to the regulations applicable to commercial customers to the extent that they are making use of a device suitable for commercial use, including in part.
- Transmission of a copy of proof of purchase is a prerequisite for guarantee claims against us or one of our dealers. For verification of the guarantee refer to the note on handling a guarantee below.
- For quick processing of guarantee claims, please inform us immediately in writing upon noticing defects, and include a fault description and photos where applicable.
- No guarantee is given for defects due to non-adherence to the operating instructions, improper treatment or normal wear and tear of the device. Guarantee claims are also excluded in terms of brittle components or expendables such as seals or similar. Finally, guarantee claims are excluded where work is performed on the device by nonauthorised parties.

Handling:

Should your device display any defects within the guarantee period, please inform us of your guarantee claim. The fastest and most convenient option is to return the device or the notice of defect to the dealer/agent responsible or directly to us:

Email to: verkauf@speidel-behaelter.de or by fax to: 0049 7473 9462 99

Please provide us with your **full address including contact details**. In addition, we require the **type designation** of the device in question, a short **fault description** including **photos**, **where applicable**, the **purchase date (copy of invoice)** and the dealer from whom you purchased the new device.

After verifying your notification of defect, we will contact you as soon as possible to agree the next step. Please, under no circumstances, send us your device by Carriage Forward.





de	Sollte die beiliegende Betriebsanleitung nicht in einer für Sie verständlichen Sprache vorliegen, so kontaktieren Sie diesbezüglich bitte Ihren zuständigen Händler.		
en	If you don't have a manual in any comprehensible language, please contact your local dealer or distributor.		
fr	Si les instructions accompagnant dans une langue qu'ils comprennent, vous donc s'il vous plaît		
fr	contacter votre revendeur local.		
es	Si las instrucciones que acompañan estar en un idioma que comprendan, que por favor contacte a su		
	distribuidor local.		
pt	Se as instruções que acompanham estar em uma linguagem que eles entendem, você por favor contacte o seu revendedor local.		
pl	Jeśli instrukcje towarzyszące są w języku, który rozumieją, tak, proszę skontaktuj się z lokalnym		
	dealerem.		
	Hvis instruksjonene som følger med være på et språk de forstår, du så ta kontakt med din lokale		
no	forhandler.		
fi			
sv	Om instruktioner vara på ett språk de förstår, behaga dig så kontakta din lokala återförsäljare.		
da	Hvis anvisningerne ledsager være på et sprog, de forstår, så du bedes kontakte din lokale forhandler.		
	Se le istruzioni che accompagnano in una lingua che capiscono, ti prego pertanto di contattare il		
it	rivenditore locale.		
-1	Εάν οι οδηγίες που συνοδεύουν να είναι σε γλώσσα που κατανοούν, σας γι 'αυτό παρακαλώ		
el	επικοινωνήστε με τον τοπικό σας αντιπρόσωπο.		
hu	Ha a mellékelt használati utasításnak kell olyan nyelven, amit megértenek, akkor ezért kérjük,		
IIu	forduljon a helyi forgalmazóhoz.		
nl	Als de instructies die bij in een taal die zij begrijpen, je zo kunt u contact opnemen met uw lokale		
111	dealer.		
ro	Dacă vă lipsește manualul de instructiuni într-un limbaj accesibil, vâ rugăm să contactați distributorul local		
ru	Если Вы не нашли инструкцию на доступном Вам языке, пожалуйста свяжитесь с вашим местным диллером или дистрибьютором.		
sk Ak Návody priloženej byť v jazyku, ktorému rozumie, si tak obráťte sa na miestneho predajcu.			
sl	Če navodila, ki spremljajo, so v jeziku, ki ga razumejo, zato vas prosimo, obrnite na lokalnega		
51	prodajalca.		
bg	Ако инструкциите, придружаващи се в разбираем за тях език, можете да се обърнете към		
05	местния дилър.		
sr	Ако се прате упутства бити на језику који они разумеју, тако да вас молимо да се обратите		
1	свом локалном дистрибутеру.		
hr	Ako upute prate se u jeziku koji razumiju, pa vas molimo da se obratite svojem lokalnom zastupniku.		
CS	Pokud Návody přiložené být v jazyce, kterému rozumí, jsi tak obraťte se na místního prodejce. talimatları anladıkları bir dilde olması eşlik ederseniz, bu nedenle yerel satıcınıza başvurun.		
tr			
zh	如果指示随行在他们理解的语言,所以请您联系当地的经销商。		
	命令は、彼らが理解できる言語になるに伴う場合は、そのお近くの販売店に連絡してくだ		
ja	さい。		
1,,,	지침 그들이 이해하는 언어에 동행하는 경우, 당신은 귀하의 지역 대리점에 문의하시기		
ko	바랍니다.		
th	หากคำแนะนำการประกอบอยู่ในภาษาที่พวกเขาเข้าใจคุณดังนั้นโปรดติดต่อตัวแทนจำหน่ายในประเทศ		
	ุ ภองษ์ซ - พ เนษ เหต่อน เบ เวกาจนอกออิเหม เฉ เทพ เนเก เก เร่าผู้เหต่อนหน้ามักต่อดาแก่น เทน เก เหต่าจะเทษ		
vi	Nếu các hướng dẫn đi kèm có trong một ngôn ngữ mà họ hiểu, bạn nên xin vui lòng liên hệ đại lý địa		
	phương của bạn.		
L	L		